


PROPOSED SECTION
scale 1:50 @ A1

NOTES

- All dimensions and levels are to be checked on site.
- Any discrepancies are to be reported to the Digital Architect Services Ltd before any work commences.
- This drawing shall not be scaled to ascertain any dimensions. Work to figured dimensions only.
- This drawing shall not be reproduced without express written permission from Digital Architect Services Ltd.
- Title overlay drawings and ownership boundaries are produced using all reasonable endeavors. Digital Architect Services Ltd cannot be responsible for the accuracy or scale discrepancy of base plans supplied to them.



- ROOF TYPE 1**
NEW FLAT ROOF TO EXTENSION
- Required U-value 0.18W/m²K (as designed 0.18W/m²K)
 - Plasterboard fixed to timber structure
 - Timber joists 120x72 at 400mm centers - TBC by SE
 - Fittings set to 1.80
 - 18mm WBP deck
 - Tyvek AirGuard VCL or equal approved
 - 120mm Kinspan Thermafloor TR27 LPC/FM or equal approved
 - Single Ply membrane

- ROOF TYPE 2**
NEW FLAT ROOF TO MAIN HOUSE
- Required U-value 0.18W/m²K (as designed 0.18W/m²K)
 - Plasterboard fixed to timber structure
 - Timber joists 195x72 at 400mm centers
 - Fittings set to 1.80
 - 18mm WBP deck
 - Tyvek AirGuard VCL or equal approved
 - 120mm Kinspan Thermafloor TR27 LPC/FM or equal approved
 - Single Ply membrane

- FLOOR TYPE 1**
EXISTING FLOOR
- Existing floor structure and substrate to be retained and refurbished.
 - Dust and debris to be removed from voids.
 - New damp proof membrane Visqueen EcoMembrane or equal approved
 - 60mm Celotex GA4000 Insulation or equal approved
 - 75mm sand/cement screed
 - Finish TBC by client

- FLOOR TYPE 2**
NEW BEAM & BLOCK FLOOR TO EXTENSION
- Existing earth compacted to Structural Engineers details.
 - Void for ventilation connected to existing void of the main house.
 - Precast concrete beam & block - TBC by SE
 - Damp proof membrane Visqueen EcoMembrane or equal approved
 - 125mm Celotex XR4000 Insulation or equal approved
 - 65mm screed.
 - Finish TBC by client

- FLOOR TYPE 3**
EXISTING TIMBER FLOOR TO FIRST FLOOR ABOVE PLAYROOM
- All ceiling boards to be replaced and new insulation to be fitted between floor joists - 100mm Rockwool RWA45 or equal approved with 12.5mm soundbloc boards screwfixed below.

- FLOOR TYPE 4**
NEW BEAM & BLOCK FLOOR TO FRONT EXTENSION
- Existing earth compacted to Structural Engineers details.
 - 150mm Type 1 Hardcore - to SE design
 - Damp proof membrane Visqueen EcoMembrane or equal approved
 - 150mm RC30 slab A193 mesh top (40mm cover) - to SE design
 - 125mm Celotex XR4000 Insulation or equal approved
 - 75mm screed
 - Finish TBC by client.

- WALL TYPE 1**
NEW TIMBER FRAME WALLS
- 20mm Siberian Larch timber clad by Russwood or equal approved fixed vertically.
 - 75 mm cavity for battens and counter battens
 - 95mm sw timber studs @ 400mm c/c's fully filled with Rockwool batts with 9mm OSB sheathing over with TYVEK 'House wrap' paper with 50mm air cavity created by battens and counter battens.
 - 80mm insulated plasterboard - Celotex GA4000 rigid PIR insulation with skim finish.
 - Internal finish TBC by client.

- WALL TYPE 2**
NEW INTERNAL MASONRY WALLS
- 12.5mm Plasterboard on dabs with skim finish
 - 215mm mass block wall (min 7N/mm²)
 - 12.5mm Plasterboard on dabs with skim finish

- WALL TYPE 3**
EXISTING EXTERNAL TIMBER FRAME WALLS
- K-Rend Silicone finish applied as per manufacturer's spec
 - 35mm Celent C3 Woodwool insulation board
 - Retain existing structure and add OSB linings if missing to external face of wall.
 - 100mm Rockwool insulation between existing timber studs.
 - 75mm Celotex FR5000 rigid PIR insulation to inner face of existing structure. Joints taped and sealed as VCL.
 - Waterproof wall tile substrate to tiled wet areas(wedi-board /schluter kerdi board)
 - Finish TBC by client

- WALL TYPE 4**
EXISTING GROUND FLOOR MASONRY WALLS
- 20mm Siberian Larch timber clad by Russwood or equal approved fixed vertically.
 - 75 mm cavity for battens and counter battens
 - 100mm block work (min 7N/mm²) inner leaf
 - 100mm insulated plasterboard - Celotex GA4000 rigid PIR insulation to inner face of existing structure with skim finish

- WALL TYPE 5**
NEW INTERNAL PARTITIONS - NON-LOAD BEARING
- Softwood studs, ungraded 75 x 50 mm
 - General spacing: 400 mm with sole plates, head plates, noggins, etc. and additional noggins and 18mm WBP plywood, where required to support fixtures and fittings, e.g. kitchens, bathrooms and utilities.
 - Preservative treatment: Required in wet areas only
 - Plasterboard backings to stud partitions:
 - Type: with 12.5mm plasterboard (moisture resistant board to kitchens, bathrooms and utilities) with a min. density of 10kg/m³ and skim finish to both sides.
 - Waterproof wall tile substrate to tiled wet areas (wedi-board /schluter kerdi board)
 - Insulation between studs: with 50mm Rockwool Flexi (or equal approved) between studs, with a min. density of 10kg/m³. Finish TBC by client.

Rev	Description	Date	Status

drawing stage	Building Regulations
drawing status	Approval

client
Private

project
Private

drawing title
Proposed Section

date	23/09/2019	drawn	CL
scale	1:50 @A1	checked	CL


DIGITAL ARCHITECT SERVICES
Adfield Hub Business Centre, Outram Street,
 Sutton in Ashfield, Nottingham NG17 4TU
 T: 0162 334 8332, www.digitalarchitectservices.co.uk

Job No	DWG No	Rev
007/01	A.03.04	